



# Dominator Series




Perfect for:

Rental Stores • Shopping Centers • Trucking • Schools • Marinas • Warehouses • Hospitals • Chemical Processors



*The Dominator is built tough for rental and industrial uses, providing hot and cold water cleaning power in a compact, maneuverable design.*



**CONTROL PANEL**  
Simple control panel makes for easy and convenient operation.



**COIL SYSTEM**  
Our exclusive "Cool Touch Coil" actually forms the combustion chamber, eliminating troublesome insulation and outside hot spots. It also allows for better air flow which in turn provides better fuel combustion and efficiency.



**ACCUMULATOR ASSEMBLY**  
The All American Accumulator Assembly, used on models with 2500 PSI or more, effectively manages high-pressure flow conditions that may ordinarily cause system failure.



**OPTIONAL HOSE REEL**  
No more tangled hoses with our optional hose reel. The Dominator hose reel provides versatility by pivoting a full 360° and allowing up to 100' of hose.

**MODEL #**

Gasoline Powered	GPM	PSI	HP	ENGINE	START	BURNER	COIL	BTU's	FUEL CONSUMPTION	DIMENSION	WEIGHT
DH3025SRDOF*	3.0	2500	7	ROBINS	PULL	OIL FIRED	96', 1/2", Sch. 80	175,000	1.10 GPH	27"L x 39"W x 39"H	325
DH3030HDOF	3.0	3000	9	HONDA	PULL	OIL FIRED	126', 1/2", Sch. 80	315,000	1.75 GPH	48"L x 32"W x 39"H	560
DH4030HDOF	4.0	3000	11	HONDA	ELECTRIC	OIL FIRED	126', 1/2", Sch. 80	434,000	2.25 GPH	48"L x 32"W x 39"H	560
DH3540HDOF	3.5	4000	13	HONDA	ELECTRIC	OIL FIRED	126', 1/2", Sch. 80	434,000	2.25 GPH	48"L x 32"W x 39"H	560
Electric Powered Direct Drive	GPM	PSI	HP	VOLTS/PHASE	AMPS	BURNER	COIL	BTU's	FUEL CONSUMPTION	DIMENSION	WEIGHT
DH2015SEDOD*	2.0	1500	2	115/1	20	OIL FIRED	96', 1/2", Sch. 40	175,000	1.10 GPH	27"L x 39"W x 39"H	325
DH3010SEDOD*	3.0	1000	2	115/1	20	OIL FIRED	96', 1/2", Sch. 40	175,000	1.10 GPH	27"L x 39"W x 39"H	325
DH3020SEDOA*	3.0	2000	4	220/1	20	OIL FIRED	96', 1/2", Sch. 40	175,000	1.10 GPH	27"L x 39"W x 39"H	325
Electric Powered Belt Drive	GPM	PSI	HP	VOLTS/PHASE	AMPS	BURNER	COIL	BTU's	FUEL CONSUMPTION	DIMENSION	WEIGHT
DH2015EBOD	2	1500	2	115/1	20	OIL FIRED	126', 1/2", Sch. 40	170,000	1.25 GPH	48"L x 32"W x 40"H	420
DH3010EBOD	3	1000	2	115/1	20	OIL FIRED	126', 1/2", Sch. 40	315,000	1.75 GPH	48"L x 32"W x 40"H	420
DH4023EBOA	4	2300	6	220/1	25	OIL FIRED	126', 1/2", Sch. 80	434,000	2.25 GPH	48"L x 32"W x 40"H	450
DH4030EBOA	4	3000	8	220/1	35	OIL FIRED	126', 1/2", Sch. 80	434,000	2.25 GPH	48"L x 32"W x 40"H	450
Propane Electric Powered Direct Drive	GPM	PSI	HP	VOLTS/PHASE	AMPS	BURNER	COIL	BTU's	FUEL CONSUMPTION	DIMENSION	WEIGHT
DH2015EDPD	2.0	1500	2	115/1	20	PROPANE	126', 1/2", Sch. 40	170,000	2.75 GPH	48"L x 32"W x 40"H	450
DH3020EDPA	3.0	2000	4	220/1	20	PROPANE	126', 1/2", Sch. 40	315,000	3.50 GPH	48"L x 32"W x 40"H	450

\* Dominator II

**STANDARD FEATURES**


- Heavy duty roll cage frame with lifting bar
- Stainless steel coil wrap & control panel
- Heavy-duty triplex plunger oil bath pump
- Corrosion-proof 8 gal fuel tank (4 gal on Dominator II)
- Fuel water separator
- Pulsation dampener
- Pneumatic tube wheels
- Adjustable axles for balance of weight
- Detergent injector
- 50' high pressure hose with quick disconnects
- Four color-coded quick-change spray nozzles
- Dual lance wand for variable pressure
- Hose reel mounting bracket

**OPTIONS**

- Hour meter
- Front swivel casters
- Steam option
- Adjustable temperature control
- Auto on/off with 30 sec. delay (electric models only)
- Hose reel
- UL1776 listed
- Painted coil wrap
- Dominator II available with up to 315,000 BTU

**5 - 1 YEAR LIMITED WARRANTY**

- 5 years on pump, Cool Touch Coil and frame
- 2 years on gasoline engines
- 1 year – 90 days on remaining components



GSA Contract GS07F-0302N